


Module Relaxation Block TITAN II Bluetooth GATE V2 front wiring

https://sport-attitude.com//en/produit-17837-Module-Relaxation-Block-TITAN-II-Bluetooth-GATE-V2-front-wiring















	SKU	Designation	French Law	MSRP
ĺ	A69411	Module Relaxation Block TITAN II Bluetooth GATE V2 front wiring	Vente libre	198.00 € incl. tax 138.60 € incl. tax

The essential Titan Gate now available in Bluetooth

The kit contains:

- 1 x Mosfet TITAN II Bluetooth T-dean
- 1x Installation Kit
- 1 x Gate Titan II Patch

Compatible accessories:

- Power Cable (GEL BLASTER / Power Charger / Tracer)
- Cable for single HPA solenoid
- HPA Dual Solenoid Cables
- Splitter ready to connect many accessories (you can connect 1x power cable and 2x I/O cable)
- Universal I/O cable for max. 2 accessories (bolt-catch, loader sensor, flashlight...)
- Bolt-catch with button and cable (ready to plug in)
- Magazine sensor with cable (ready to connect

Built-in Bluetooth 5.2 technology gives you direct access to TITAN settings, AEG telemetry and the ability to use a smartwatch, STATUS and other future GATE Ecosystem devices. The innovative gear sensor not only counts gears, but also determines the direction of rotation of a gear as the first in the world, giving you the most precise cycle control of AEGs. The stunning optical trigger sensor lets you fine-tune a hair's trigger with incredible precision: 50 levels of sensitivity for the first millimeter of trigger movement, retaining the benefits of the TITAN V2 sensor. **The TITAN II Bluetooth**® is equipped with a multifunctional port ready to connect additional accessories such as bolt catch, loader sensor, tracer in the hop-up chamber and others...

What makes the TITAN II Bluetooth® so special?

- All-new patented gear sensor, the world's first, detects each tooth and the direction of gear movement, allowing extremely precise cycle control
- Mechanical protection of trip sensors increases reliability. Potential damage to trigger sensors is now covered under warranty.
- Ultra-precise telemetry measurements thanks to the new current sensor
- Pre-cocking can be set in %
- Built-in voltage boost converter. Trouble-free operation at low temperatures
- Multifunctional programmable port ready to connect:
- Hop-up chamber for plotter and sensors
- Lock button
- Convertible for the HPA (one solenoid or dual solenoid, you need an extra cable or two, sold separately)
- Electric magazine
- Store sensor
- Flash light

User-friendly GCS app for iOS, Android, macOS, Windows, watchOS, Wear OS

TITAN II can be connected to a smartwatch.

Compatibility with the GATE ecosystem, including GATE STATUS and future hop-up chamber with tracer Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.