

GATE TITAN II Basic Bluetooth for GB V2 HPA - Rear wiring

https://sport-attitude.com/en/produit-17857-GATE-TITAN-II-Basic-Bluetooth-for-GB-V2-HPA-Rear-wiring









SKU	Designation	French Law	MSRP
A69412	GATE TITAN II Basic Bluetooth for GB V2 HPA - Rear wiring	Vente libre	202.00 € incl. tax

The brand new TITAN II Bluetooth® for GB V2 HPA -Basic version

This HPA version will allow you to connect 1 to 2 solenoids, which makes it compatible with:

- Polarstar Jack
- Polarstar F2
- Gate Pulsar
- Wolverine Inferno gen II
- Wolverine Reaper gen II *electro-pneumatic version*
- Wolverine Hydra
- Redline N7 *electro-pneumatic version*

Kit Contents:

- 1 x MOSFET TITAN II Bluetooth - JST
- 1 x JST to T-dean conversion cable
- 1 x cable to connect 1 additional solenoid
- 1x Installation Kit
- 1 x Gate Titan II Patch

Built-in Bluetooth 5.2 technology gives you direct access to TITAN settings, AEG telemetry and the ability to use a smartwatch, STATUS and other future GATE Ecosystem devices. The innovative gear sensor not only counts gears, but also determines the direction of rotation of a gear as the first in the world, giving you the most precise cycle control of AEGs. The stunning optical trigger sensor lets you fine-tune a hair's trigger with incredible precision: 50 levels of sensitivity for the first millimeter of trigger movement, retaining the benefits of the TITAN V2 sensor. **The TITAN II Bluetooth®** is equipped with a multifunctional port ready to connect additional accessories such as bolt catch, loader sensor, tracer in the hop-up chamber and others...

What makes the TITAN II Bluetooth® so special?

- All-new patented gear sensor, the world's first, detects each tooth and the direction of gear movement, allowing extremely precise cycle control
- Mechanical protection of trip sensors increases reliability. Potential damage to trigger sensors is now covered under warranty.
- Ultra-precise telemetry measurements thanks to the new current sensor
- Pre-cocking can be set in %
- Built-in voltage boost converter. Trouble-free operation at low temperatures
- Multifunctional programmable port ready to connect:
- Hop-up chamber for tracer and sensors
- Lock button
- Not convertible to AEG version
- Electric magazine
- Store sensor
- Flash light

User-friendly GCS app for iOS, Android, macOS, Windows, watchOS, Wear OS

TITAN II can be connected to a smartwatch.
Compatibility with the GATE ecosystem, including GATE STATUS and future hop-up chamber with tracer

The lowest current consumption on the market. The deep sleep mode with a current consumption of only 0.1 mA prevents battery drain (3 times lower consumption than current ETUs, which already had the lowest current consumption on the market).

Compatible accessories:

- Power Cable (GEL BLASTER / Power Charger / Tracer)
- Cable for single HPA solenoid
- HPA Dual Solenoid Cables
- Splitter ready to connect many accessories (you can connect 1x power cable and 2x I/O cable)
- Universal I/O cable for max. 2 accessories (bolt-catch, loader sensor, flashlight..)
- Bolt-catch with button and cable (ready to plug in)
- Chargers sensor with cable (ready to connect)

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.