



**SPECIALE  
LOISIR**

SKU	Designation	French Law	Lumens	Mounting	MSRP
A61237	Skywoods RAFALE tactical light	Vente libre	600	21mm rail	46.70 € incl. tax

### 600 Lumen tactical flashlight.

- LED: CREE XPL-V6
- Yield: High 500LM
- Lighting mode: High, strobe
- Duration of use: 2 hours
- Beam distance: High?116M
- Housing material: aluminum alloy
- Water resistance: IP65
- Shock resistance: 1m
- Battery: 1x CR123A
- Application rail: Suitable for 21mm rails
- Device dimensions: 32.6\*29.5\*62.5mm
- Net weight: 74.5 g (with battery)
- **Durable Material:**
  - Anodized aluminum alloy shell provides exceptional durability for rugged use.
- **Versatile Lighting Modes:**
  - Two lighting modes available: fixed and strobe, ensuring flexibility of use adapted to various situations.
- **High-performance LED lighting:**
  - Equipped with an XPL-V6 LED, this lamp offers a stable brightness of ?3200Lux with a color temperature of 5700-7000k.
- **Battery Life:**

- The lamp offers two durations of use: 2 hours in fixed mode and 5 hours in strobe mode, ensuring reliable autonomy.
- **Compact and Portable Design:**
  - Compact dimensions of 32.6 29.5 61mm and a net weight of 74.5g with battery, providing optimal portability.
- **Resistance to External Conditions:**
  - Aluminum alloy housing material, waterproof to IP66 standard, shock resistant up to 1mm.
- **Non-Rechargeable Battery:**
  - Powered by a CR123 alkaline battery, providing a reliable and convenient power source (non-rechargeable).
- **Ambidextrous Switch:**
  - Both sides of the lamp feature an ambidextrous switch allowing easy control of the light. One press activates Steady On mode, while two quick presses activates strobe mode.
- **Compatibility with Firearms:**
  - Designed to be safe and suitable for firearms with a MIL-STD-1913 (Picatinny) rail, providing wide applicability.

*Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.*