



GATE



SKU	Designation	French Law	MSRP
A69440	Aster Rear Wiring	Vente libre	127.00 € incl. tax
A69441	Aster Front Wiring	Vente libre	127.00 € incl. tax

One of the most reliable and versatile ETUs on the market

Extraordinary value for money:

- ASTER II Bluetooth® gives you total flexibility thanks to Bluetooth® 5.2 and compatibility with AEG and HPA. You can update your firmware and get new options, connect additional accessories, check telemetry. Now – straight to the shelf. No additional cost.
- GCS app for iOS, Android, macOS or Windows
- GCS app for your smartwatch (Wear OS or watchOS) – real-time data like BB counters and remote triggering!
- Compatibility with AEG and HPA single solenoid motors
- Hair trigger – up to 35 trigger sensitivities for the first millimeter (0.04 in) of movement and up to 680 in the full range
- Configurable trigger reset (hysteresis)
- High-end automatic pre-cocking
- Free firmware updates over the Internet
- ASTER II Bluetooth® is part of the GATE ecosystem
- Lowest current consumption on the market – deep sleep mode with only 140uA current consumption prevents battery drain
- Integrated voltage boost converter allows trouble-free operation with weaker batteries and increases switching efficiency
- 3.75V Ready – ASTER II Bluetooth® operates at very low voltage (even 1.2V while shooting), which is important in high setting AEGs, where the voltage under load drops significantly
- Sensor supporting Infinite Torque-up, DSG, SSG, 19-tooth and standard gears
- The possibility of using a mechanical trigger lock
- Wide compatibility with brushless motors – works perfectly with all common brushless motors, even with 11.1 V batteries
- Multifunctional programmable I/O port – connects lock sensor, magazine sensor, etc.

What makes ASTER II Bluetooth® so special?

- Everything you need, ready to use
- Adjustable Quantum 2 trigger included in the kit.
- Adjust the trigger travel with the screw and the trigger sensitivity in the app.
- Integrated Bluetooth® 5.2
- Noise-resistant trigger detection algorithm
- Integrated "Hair-trigger" system (35 trigger sensitivities for the first millimeter (0.04 in) of movement and up to 680 in the full range)
- Additional protection against interference thanks to multi-layer PCB with EMC shielding
- Automatic pre-arming: 0%, 20%, 40%, 60%, 80%, 100%
- Trigger sensitivity adjustment without any limitations – plus you can now adjust the trigger reset (hysteresis)
- Improved cycle detection
- Active brake adjustment: adaptive / 1-100%
- 343 selection modes. All possible combinations of: SAFE, SEMI, BURST, BINARY, BURST/AUTO, AUTO & SEMI RAMPING
- The GCS app allows firmware updates via the Internet, meaning instant application of enhancements.
- The ASTER II Bluetooth® are now compatible with the QUANTUM TRIGGER: (Quantum Trigger 1 (QT: 1A1, 1B1, 1C1, 1E1) Quantum Trigger 2 (QT-2A1) – adjustable overtravel movement with ASTER II Bluetooth® screw)
- Supply voltage range 3.75-12.9 V
- Current consumption: 20 mA
- Low power mode: 130 µA
- Dimensions (Length x Width x Height): 43.8 mm x 28.7 mm x 5.5 mm
- Product weight: 23.4g

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.